

BALAD

LAMP H.10 IN.


DESIGN BY TRISTAN LOHNER

ITEM 3612



TESTING STANDARDS - Upon request

TECHNICAL FEATURE - STRUCTURE



Aluminum handle

Polyethylene diffuser

Lighting intensity : 2 neutral whites (100 & 50%) + 1 cool white (100%) + 1 candle-style flickering mode + OFF

T° color : 1 candle-style warm white (2300 K°), 1 neutral white (4000 K°) and 1 cool white (6000 K°)

Technology LED - 0.5 W

Luminous flux : 40 lm

Min. Battery life : 7 h - Max. : 14 h

Rechargeable (5h)

Type of power supply : USB - Cable (supplied) 2 IN.

Controlled with switch

Bypass to prevent battery damage during wired use

IP44 (ingress protection) :: IK10 (impact resistance) :: CE :: FCC :: During charging, the lamp automatically turns itself off in order to protect the lifespan of the Led

361000 - H.10 IN. SET (6 colors)

36111 - H.10 IN. SET (6 monochrome)

Powered by Smart & Green

1 lb

FURTHER INFORMATION

BALAD

LAMP H.15 IN.


DESIGN BY TRISTAN LOHNER

ITEM 3622



TESTING STANDARDS - Upon request

TECHNICAL FEATURE - STRUCTURE



Aluminum handle
 Polyethylene diffuser
 Lighting intensity : 2 neutral whites (100 & 50%) + 2 cool whites (100% & 50%) + 1 candle-style flickering mode + OFF
 T° color : 1 candle-style warm white (2300 K°), 1 neutral white (4000 K°) and 1 cool white (6000 K°)
 Technology LED - 2.5 W
 Luminous flux : 150 lm
 Min. Battery life : 9 h - Max. : 16 h
 Rechargeable (7h)
 Type of power supply : USB - Cable (supplied) 2 IN.
 Controlled with switch
 Bypass to prevent battery damage during wired use
 IP44 (ingress protection) :: IK10 (impact resistance) :: CE :: FCC :: During charging, the lamp automatically turns itself off in order to protect the lifespan of the Led
 362000 - H.15 IN. SET (6 colors)
 3621 - H.15 IN. SET (6 monochrome)
 Powered by Smart & Green

3 lb

FURTHER INFORMATION